

PRESSURE-RATED HATCH

100% Customizable

Durable Construction

SMARTER ACCESS FOR INDUSTRIAL MACHINERY

Our Pressure-Rated Hatches are specifically designed to improve access to material flow and mechanical parts – perfect for conveyors, refineries, blade changeouts, coal mills, pulverizers and mines. Custom sizes, shapes and colors are available to fit your unique application.

REDUCES DEBRIS BUILDUP

- The flush interior surface reduces erosion and the accumulation of static, flammable fuel dust deposits
- Its low-profile frame and gasketing reduces dust and debris along the full perimeter of the opening

EASY INSTALLATION AND OPERATION

- Unlike traditional pyrite access doors and hatches, our hatches operate with pivoting swing latch bolts and spin down nuts to secure the hatch in place
- This hatch can be released and opened in minutes by the use of a 3/4" wrench
- · Features minimal latching for quick, easy access
- Stocked sizes are available for fast shipping

DESIGNED FOR A LONG SERVICE LIFE

- Meets NFPA Standard 8503 1997 (2-6 Pulverizer System) component design requirements
- Designed for a normal interior operating pressure of 2 psi and built to withstand a one-time potential 50 psi load without releasing
- · Features heavy-duty construction and stainless steel hinges
- · Fabricated from mild steel with a red oxide primer finish

Rely on PS Access Solutions[™] to build a Pressure-Rated Hatch that exceeds your performance expectations. All Pressure-Rated Hatches are 100% customizable to meet your specific application.





